

Product Code: 08911RDA
 Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(See top of page)

2. COMPOSITION/INFORMATION ON INGREDIENTS

This product contains one or more reported carcinogens or suspected carcinogens which are noted below and in Section 11.

This product contains a component or components that are Federally classified as a hazardous air pollutant.

Component/Exposure Limits	CAS#	% by Wt.
VM&P NAPHTHA	64742-89-8	30-40%
ACGIH TLV/TWA - 300 PPM OSHA PEL - 300 PPM, OSHA STEL- 400 PPM CONTAINS: 1.5% Octane, 1.16% n-Heptane		
TOLUENE	108-88-3	7.82
ACGIH TLV/TWA - 20 PPM, 75MG/M3 OSHA PEL: 200PPM, STEL: 300PPM, 500PPM(CEIL)* * For a 10 minute interval during an 8-hour shift. OTHER LIMITS: NIOSH REL: 100PPM(TWA), 375MG/M3(TWA) NIOSH STEL/CEIL: 150PPM, 560MG/M3		
BUTYL ACETATE	123-86-4	7.55
ACGIH TLV/TWA - 150 PPM, 713MG/M3, STEL/CEIL:200PPM OSHA PEL: 150PPM, 710MG/M3 OTHER LIMITS: NIOSH REL: 150PPM, 710MG/M3; STEL/CEIL: 200PPM(TWA)		
ALIPHATIC HYDROCARBON	64742-47-8	3.97
ACGIH TLV/TWA - Not Established OSHA PEL - Not Established OTHER LIMITS: MANUFACTURE'S RECOMMEND LIMITS: 213PPM(TWA), 1200MG/M3(TWA)		
XYLENE (PURE)	1330-20-7	2.84
ACGIH TLV/TWA - 100 PPM, 434 MG/M3; STEL: 150 PPM OSHA PEL - 100 PPM(TWA), 435 MG/M3(TWA) OTHER LIMITS: NIOSH REL: 100 PPM(TWA), 435 MG/M3(TWA)		
LIGHT AROMATIC NAPHTHA	64742-95-6	1.06
ACGIH TLV/TWA - Not Established OSHA PEL - Not Established		
ETHYLBENZENE	100-41-4	.486
ACGIH TLV/TWA - 100 PPM, 434 MG/M3 STEL: 125PPM OSHA PEL - 100 PPM, 435 MG/M3 OTHER INFORMATION: Listed by IARC as Group 2B,		

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

possibly carcinogenic to humans. See Section 11.

OTHER LIMITS:

NIOSH REL: 100 PPM(TWA), 435 MG/M3(TWA)

STYRENE MONOMER 100-42-5 .16

ACGIH TLV/TWA - 20 PPM, 85MG/M3; STEL/CEIL:40PPM

OSHA PEL - 100 PPM, STEL CEIL - 200 PPM, 600PPM*

OTHER INFORMATION:

Listed by IARC as Group 2B Carcinogen.

See section 11 for more information.

Skin Notation: Potential for dermal absorption.

OTHER LIMITS:

NIOSH REL/TWA: 50PPM,215MG/M3; STEL/CEIL:100PPM

NAPHTHALENE 91-20-3 .119

ACGIH TLV/TWA - 10 PPM, 52MG/M3, STEL:15PPM

OSHA PEL - 10 PPM, 50MG/M3

OTHER LIMITS:

NIOSH REL: 10PPM(TWA), 50MG/M3(TWA)

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if inhaled. May cause the following effects:

Nose, throat and respiratory tract irritation. Allergic respiratory reaction.

May cause lung damage. Eye and skin irritation. Allergic skin reaction.

FLAMMABLE LIQUID

Keep away from heat, sparks, and flame.

Vapors may cause flash fire.

Toxic gases/fumes are given off during burning or thermal decomposition.

EYE CONTACT:

Severe irritant. Prolonged contact may result in chemical

burns to the eyes. Blindness may occur.

SKIN CONTACT:

Severe irritant. Contact with skin causes severe irritation

and pain. Prolonged contact may result in chemical burns.

Product may be absorbed through the skin in harmful amounts.

PRIMARY ROUTES OF ENTRY:

Skin absorption.

Dermal and inhalation.

INGESTION:

If swallowed, consult a physician immediately.

Date Printed: 1/24/2008

Page: 3

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

INHALATION:

Anesthetic. Can cause irritation of the respiratory tract or acute nervous system depression characterized by the following progressive steps if severe overexposure is continued: headache, dizziness, staggering gait, confusion or unconsciousness.

CHRONIC INFORMATION:

See Section 11.

CARCINOGENICITY:

See Section 11.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Asthma and other respiratory ailments; chemical sensitization.

4. FIRST AID MEASURES

EYE CONTACT:

Flush immediately with large amounts of running water for at least 15 minutes while lifting eyelids. Take to a physician for medical treatment.

SKIN CONTACT:

Wash affected areas with soap and water. Remove contaminated clothing and wash before reuse. Consult a physician if irritation develops or persists.

INGESTION:

If swallowed, CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

INHALATION:

Remove from exposure. Restore breathing. Keep warm and quiet. Notify a physician.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION PROPERTIES:

FLASH POINT (deg.F):

45

METHOD:

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

Tag Closed Cup

FLAMMABLE LIMITS % :

Lower limit: 0.9

Upper limit: 8.1

AUTOIGNITION TEMPERATURE:

N/A

EXTINGUISHING MEDIA:

Carbon Dioxide, Dry Chemical or Foam.

FIREFIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flames. Closed container may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near product container (even empty) because product (even residue) can ignite explosively. Full protective equipment including self-contained breathing apparatus should be worn. Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up or possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED :

Evacuate all non-essential personnel and remove all sources of ignition (flames, hot surfaces, electrical, static and frictional sparks). Ventilate area. Equip clean-up crew with appropriate protective equipment. Avoid breathing vapors. Avoid skin contact. Prevent entry into drains, sewers and waterways. Notify appropriate authorities if necessary. Contain and remove with inert absorbent and nonsparking tools.

7. HANDLING AND STORAGE

HANDLING:

Use only with adequate ventilation. Avoid prolonged breathing of vapors. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates that vapor/mist levels are below applicable exposure limits. Follow respirator manufacturer's directions for use. Use grounding and bonding connection when transferring material to prevent static discharge, fire or explosion.

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtec 24-hour Emergency Phone: 800-424-9300

Avoid free fall of liquid in excess of a few inches. Use sparkproof tools and explosion proof equipment.

STORAGE:

Do not store above 120 F or below 32 F. Store large quantities in buildings designed to comply with OSHA's 29 CFR 1910.106. Keep away from heat, sparks and open flame. Keep containers closed when not in use. Keep closures tight and upright to prevent leakage. Emptied containers may retain hazardous residue. Follow all hazard precautions in this data sheet until container is thoroughly cleaned or destroyed. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below current applicable OSHA safety and health requirements in the mixing, application and curing areas; and to remove decomposition products during welding and flame cutting on surfaces coated with this product.

RESPIRATORY PROTECTION:

When spray applied and when used in limited ventilation areas, wear a NIOSH/MSHA approved organic vapor/particulate respirator designed to remove a combination of particulate, gas and vapor. When used in confined areas or poorly ventilated areas, use a NIOSH/MSHA approved air line type respirator or hood. During sanding or grinding operations, use a NIOSH approved particulate respirator to remove solid airborne particles of sanding dust. Use NIOSH approved respirators when flame cutting, welding or hazing material coated with this product. Observe OSHA regulations for respirator use (29 CFR 1910.134). Air monitoring of the workplace may be required to determine appropriate respirator selection.

EYE PROTECTION:

Use safety eyewear with splash guards or side shields. A full face shield may be appropriate. Contact lenses should not be worn.

Date Printed: 1/24/2008

Page: 6

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

SKIN PROTECTION:

It is good industrial hygiene practice to minimize skin contact. Chemical resistant gloves are required for prolonged or repeated contact. An apron may be appropriate to protect against skin contact. Prevent prolonged skin contact with contaminated clothing. Wash contaminated clothing before reuse.

OTHER PROTECTIVE EQUIPMENT AND GUIDLINES:

Safety showers and eye wash stations should be available. Educate and train employees in the safe use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES**PHYSICAL STATE:**

Liquid.

APPEARANCE:**ODOR:**

Solvent odor.

VOC (LB/GL):

4.58 lb/gl

VOC (grams/liter):

548 g/l

WEIGHT PER GALLON:

7.4791 lb/gl

SPECIFIC GRAVITY:

.8982

%EXEMPT SOLVENT by WEIGHT:

0

%EXEMPT SOLVENT by VOLUME:

0

BOILING POINT (deg. F):

230

WATER SOLUBILITY:

Negligible.

FREEZING POINT (deg. F):

N/A

10. STABILITY AND REACTIVITY**STABILITY:**

Stable under normal conditions.

HAZARDOUS POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain the following:
Carbon Monoxide, Carbon Dioxide and other toxic vapors depending upon the temperature reached.

INCOMPATIBILITIES (MATERIALS TO AVOID):
Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

Toluene:

LD50 Oral Rat = 5000mg/kg
LC50 Inhalation Rat = 8000 ppm for 4 hours
LD50 Dermal Rabbit = 14000mg/kg

Xylene (Mixed Isomers):

LD50 Oral Rat = 4300mg/kg
LC50 Inhalation Rat = 6700 ppm for 4 hours
LD50 Dermal Rabbit = >2000mg/kg

Ethyl Benzene:

Oral Rat LD50 = 3.5 g/kg
Dermal Rabbit LD50 = 17 g/kg

Has not been tested as a whole for acute effects.

CHRONIC EFFECTS:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage, liver and kidney damage. Long term overexposure effects are not currently known. There are reports that long-term repeated exposure to Xylene may result in some loss of hearing. There are reports that long-term repeated exposure to Toluene may result in some loss of hearing.

Has not been tested as a whole for chronic effects.

CARCINOGENICITY:

Contains Ethylbenzene which IARC has listed as Group 2B, possibly carcinogenic to humans, based upon laboratory animal studies.
Contains Styrene which has been shown to cause cancer in laboratory animals by ingestion and is listed as a suspect carcinogen by IARC (group 2B).

Date Printed: 1/24/2008

Page: 8

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

Has not been tested as a whole for carcinogenicity effects.

MUTAGENICITY:

Has not been tested as a whole for mutagenicity effects.

REPRODUCTIVE EFFECTS:

Has not been tested as a whole for reproductive effects.

DEVELOPMENTAL EFFECTS:

Has not been tested as a whole for developmental effects.

12. ECOLOGICAL INFORMATION

ECOLOGICAL EFFECTS:

Has not been tested as a whole for ecological effects.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

Recycle, fuel blend or incinerate.
Dispose of in accordance with applicable laws and regulations. It is the responsibility of the owner of the waste to dispose of it properly. Laboratory analysis is recommended to profile the waste for proper disposal determination.

U.S E.P.A WASTE NUMBER AND DESCRIPTION:

D001 Waste Paint

HAZARDOUS WASTE CHARACTERISTICS:

Ignitable.

14. TRANSPORT INFORMATION

UN NUMBER:

UN 1263

DOT PROPER SHIPPING NAME:

Paint

DOT HAZARD CLASS:

3

DOT LABEL:

Flammable Liquid

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

DOT PACKAGING GROUP:
PG II

U.S. POSTAL SERVICE:
Will not handle.

15. REGULATORY INFORMATION

(Not meant to be all inclusive - selected regulations represented)

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

CAS#100-41-4	Ethyl Benzene
CAS#1330-20-7	Xylene
CAS#100-42-5	Styrene Monomer
CAS#108-88-3	Toluene
CAS#91-20-3	Naphthalene

TSCA STATUS:

All ingredients are listed on the TSCA inventory.

STATE REGULATIONS:

Toluene is listed by the State of California as a substance known to cause reproductive toxicity. The California Safe Drinking Water and Toxic Enforcement Act requires clear and reasonable warning be given before exposing any person to toluene. Toluene may also contain traces of benzene which the State of California has found to cause cancer. This product may contain chemicals that fall under individual state Right-to-Know regulatory requirements. See Section 2 for material listings. For details on regulatory requirements, contact the appropriate agency in your state.

16. OTHER INFORMATION

Date of issue: 1/24/2008

Last Revision Date: 11/23/05

HMIS Information

HEALTH: 2
FLAMMABILITY: 3
REACTIVITY: 1
PERSONAL PROTECTIVE EQUIPMENT: X

Date Printed: 1/24/2008

Page: 10

Product Code: 08911RDA
Product Name: RED POLY-ZEN ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

DISCLAIMER:

This MSDS is provided as an informational resource only. The information is received from a combination of sources, including raw material suppliers and is believed to be reliable and accurate. It does not intend to be all-inclusive and shall only be used as a guide. Changing reporting requirements and other uncontrolled variables make it impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to verify its information as well as determine the proper personal protection based on conditions of use. The buyer assumes all responsibility for the use and handling of this product in accordance with the Federal, State and Local laws and regulations. Hentzen Coatings, Inc. makes no representation or warranty regarding the accuracy of this information nor that the information or data will not change.